

CentOS

MYSQL / MARIADB commandos

[Inloggen in Mariadb] mysql -u root -p

```
CREATE USER 'username'@'localhost' IDENTIFIED BY 'password';
GRANT ALL PRIVILEGES ON *.* TO 'username'@'localhost' WITH GRANT OPTION;
CREATE USER 'username'@'%' IDENTIFIED BY 'password';
GRANT ALL PRIVILEGES ON *.* TO 'username'@'%' WITH GRANT OPTION;
FLUSH PRIVILEGES;
```

show databases;

```
CREATE DATABASE db1;
Query OK, 1 row affected (0.18 sec)
```

```
CREATE DATABASE db1;
ERROR 1007 (HY000): Can't create database 'db1'; database exists
```

```
CREATE OR REPLACE DATABASE db1;
Query OK, 2 rows affected (0.00 sec)
```

```
CREATE DATABASE IF NOT EXISTS db1;
Query OK, 1 row affected, 1 warning (0.01 sec)
```

```
SHOW WARNINGS;
+-----+-----+-----+
| Level | Code | Message |
+-----+-----+-----+
| Note | 1007 | Can't create database 'db1'; database exists |
+-----+-----+-----+
```

drop database test01;

```
SELECT User FROM mysql.user;
```

```
SELECT host, user FROM mysql.user;
```

```
SELECT host, user, password FROM mysql.user;
```

```
show grants for 'vivek'@'%';
```

```
show tables from mysql;
```

```
show full tables from mysql;
```

```
show columns from Jokes_table from test;
```

```
+-----+-----+-----+-----+-----+
Pagina 1 / 2
```

CentOS

```
| Field | Type | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| JokeID | int(11) | NO | PRI | NULL | auto_increment |
| Joke_question | varchar(500) | NO | | NULL | |
| Joke_answer | varchar(500) | NO | | NULL | |
+-----+-----+-----+-----+-----+
3 rows in set (0.001 sec)
```

```
alter user testuser identified by 'wachtwoord';
```

```
MariaDB [(none)]> select password ('wachtwoord');
+-----+
| password ('wachtwoord') |
+-----+
| *B33F1075E48B7CB3B733C3B84DACE4FBD1135C97 |
+-----+
1 row in set (0.000 sec)
```

```
MariaDB [(none)]>
```

Bijgevoegde bestanden::

Unieke FAQ ID: #1086

Auteur:: diode

Laatst bijgewerkt:11-03-2021 16:55